



Hermit Cam Systems

An original line of easily concealable pan/tilt network cameras available as a turn-key system, or as a do-it-yourself kit, the Hermit-Cam series is versatile, covert, and adaptable to a wide range of operating temperatures, voltages, enclosures, and remote modalities.

Mini Front Pivot/Front Tilt Camera system	
Power requirements	12 volt
	Approximately 350ma
Maximum dimensions at end of travels	9"H x 8W" x 5D"
Reference point	Virtual center 1" from front of lens
Maximum operating temperature	140° F
Pan range	35° from center; total 70°
Tilt range	25° from horizontal; total 50°
Motors	12 volt brush
Cameras	
Color 10X zoom	<ul style="list-style-type: none"> • 10X optical / 12X digital zoom • Lens: 3.8-38mm • f-1.8 (w) to 2.4 (t) • ¼" Image sensor • Focus: Auto with manual over ride • Auto iris • Horizontal resolution: 470TVL • Minimum sensitivity: 1 lux color (normal DSS) .1 lux color (1/4s DSS) • Operating temperature range: 5-40C
Color/black white 35X zoom	<ul style="list-style-type: none"> • 35X optical / 12X digital zoom • Lens: 3.4-119mm • f-1.4 (w) to 4.2 (t) • ¼" Image sensor • Electric Image Stabilization • Wide Dynamic Range • Focus: Auto with manual over ride • Auto iris • Horizontal resolution: 540TVL • Minimum sensitivity: .5 lux color (normal DSS) .025 lux b/w (1/2s DSS) • Operating Temperature range: 0-60C • Full-range imaging portal: 2-3"
Base price - Choose Encoder or software PTZ control option	
Encoder board	PTZ Controls compatible with View Commander and Milestone recording software, certain models NVR <ul style="list-style-type: none"> • 10X zoom • 35X zoom

© 2009 Crime Point, Inc. Specifications subject to change without notice.

www.crimepoint.net • T:888.484.9901 • F:805.388.3374

info@crimepoint.net • 355 N. Lantana St. #503, Camarillo CA 93010



Mini Front Tilt/Continuous 360° Camera system	
Power requirements	12 volt
	Approximately 350ma
Maximum dimensions at end of travels	
Tilt Reference Point	1" from front of lens
Maximum operating temperature	140 F
Pan range	Continuous 360°
Tilt range	25° from horizontal; total 50°
Motors	12 volt brush
Cameras	
Color 10X zoom	<ul style="list-style-type: none"> • 10X optical / 12X digital zoom • Lens: 3.8-38mm • f-1.8 (w) to 2.4 (t) • ¼" Image sensor • Focus: Auto with manual over ride • Auto iris • Horizontal resolution: 470TVL • Minimum sensitivity: 1 lux color (normal DSS) .1 lux color (1/4s DSS) • Operating temperature range: 5-40C
Color/black white 35X zoom	<ul style="list-style-type: none"> • 35X optical / 12X digital zoom • Lens: 3.4-119mm • f-1.4 (w) to 4.2 (t) • ¼" Image sensor • Electric Image Stabilization • Wide Dynamic Range • Focus: Auto with manual over ride • Auto iris • Horizontal resolution: 540TVL • Minimum sensitivity: .5 lux color (normal DSS) .025 lux b/w (1/2s DSS) • Operating Temperature range: 0-60C
Base price - Choose Encoder or software PTZ control option	
Encoder board	PTZ Controls compatible with View Commander and Milestone recording software, certain models NVR <ul style="list-style-type: none"> • 10X zoom • 35X zoom